SIDE BY SIDE COMBINATIONS







R R

SIDE BY SIDE COMBINATION SBSbs 7263

Ice

Maker



Bio
Fresh

No Frost


Soft System

Telescopic

Rails

3 Year Warranty





Whilst every effort is made to ensure all specifications and information in this flyer are correct at time of printing, Andi-Co Australia Pty. Ltd. reserve the right to make changes without notification. Where actual appliance measurements, specifications and ratings are crucial, we recommend that the actual appliance installation instructions that accompany each appliance be checked. Andi-Co Australia will not be liable for any loss.

Model SBSbs 7263*		7263*		
*Side by Sides comprised of two models	SGNbs 3011	SKBbs 4210		
Type Freestanding (FS) Finish	FS BlackSteel	FS BlackSteel		
Energy consumption (kWh/yr) Star rating	320 3.5	252 3.0		
Compressors	1	1		
Total capacity litres (L) - Gross I Net	304 256	403 364		
Refrigerator gross (L) Refrigerator Net (L)	-	277 247		
Freezer gross (L) Freezer net (L)	304 256	-		
BioFresh gross (L) BioFresh net (L)	-	126 117		
MagicEye control system Display	SoftTouch I LCD	SoftTouch I LCD		
Child proof setting for display & temp.	•	•		
LED standard lighting	•	•		
SlimLine handle - integrated opening device	•	•		
SoftSystem hinge - assists closure	•	•		
Door open warning signal	•	•		
Temperature alarm	•	•		
Malfunction warning signal	•	•		
Refrigerator Features				
BioFresh drawers on telescopic rails	N/A	3		
Fruit & vegetable drawer on telescopic rails	N/A	-		
SuperCool	N/A	•		
GlassLine shelves	N/A	•		
Elegant holding columns	N/A	•		
Removable VarioBoxes	N/A	•		
Bottle shelf I Egg tray	N/A	- -		
Automatic refrigerator defrosting	N/A	•		
Freezer Features				
Freezer defrosting	Frost Free	N/A		
FrostSafe system with transparent drawers	•	N/A		
Freezer drawers Ice cube drawers	8 1	N/A		
SuperFrost	•	N/A		
VarioSpace	•	N/A		
24hr freezing capacity (kg)	18	N/A		
Cold storage accumulators	2	N/A		
IceMaker	•	N/A		
Ice cube capacity (kg/24hr)	0.8	N/A		
Ice cube max. (kg)	1.5	N/A		
Stainless steel hose supplied (m)	1.5	N/A		
Technical Information				
Default hinge	Left	Right		
	220-240 1.3	220-240 1.2		
Voltage (V) Rated current (Amps)	220 2401 1.5	LEO ETO TILE		

KEY: FS = Freestanding, N/A = Not Applicable, * = Freestanding side by sides consist of two Liebherr models. These models can be purchased separately. Cavity clearance for freestanding units please allow min. 50 mm above the unit if there is no ventilation cut-out.