







## SIDE BY SIDE COMBINATION SBSbs 7353





Bio Fresh No Frost

lce Maker Soft System Telescopic Rails 3 Year Warranty



11	
300cm² Ventilation Cut-Off	
1250 10 Cut-Off	

Whilst every effort is made to ensure all specifications and information in this flyer are correct at time of printing, Andi-Co Australia Pty, Ltd. reserve the right to make changes without notification. Where actual appliance measurements, specifications and ratings are crucial, we recommend that the actual appliance installation instructions that accompany each appliance be checked. Andi-Co Australia will not be liable for any loss.

SBSbs 7353 Millimetres (mm)

Model	SBSbs	7353*
*Side-by-Sides comprised of two models	SBNbs 3210	SKbs 4210
Type I Finish	FS I BlackSteel	FS I BlackSteel
Energy consumption (kWh/yr) I Star rating	358kWh I 3.0	279kWh I 2.5
Compressors	1	1
Total capacity litres (L) - Gross I Net	321   276	405 I 391
Refrigerator gross (L) I Refrigerator net (L)	-	405 I 391
Freezer gross (L) I Freezer net (L)	150   119	-
BioFresh gross (L) I BioFresh net (L)	171 I 157	-
MagicEye control system I Display	SoftTouch I LCD	SoftTouch I LCD
Child proof setting for display & temp.	•	•
LED standard lighting	-	•
SlimLine handle - integrated opening device	•	•
Door open warning signal	•	•
Temperature alarm	•	-
Malfunction warning signal	•	•

## **Refrigerator Features**

BioFresh drawers on telescopic rails	2	-
Fruit & vegetable drawer on telescopic rails	-	2
SuperCool	N/A	•
GlassLine shelves	•	•
Elegant holding columns	•	•
Removable VarioBoxes	N/A	•
Bottle shelf I Egg tray	- I N/A	•   •
Automatic refrigerator defrosting	•	•

## **Freezer Features**

Freezer defrosting	Frost Free	N/A		
FrostSafe system with transparent drawers	•	N/A		
Freezer drawers I Ice cube drawer	411	N/A		
SuperFrost	•	N/A		
VarioSpace	•	N/A		
24hr freezing capacity (kg)	14	N/A		
Cold storage accumulators	2	N/A		
IceMaker	•	N/A		
Ice cube capacity (kg/24h)	0.8	N/A		
Ice cube stock max. (kg)	1.5	N/A		
Stainless steel hose supplied (m)	1.5	N/A		

## **Technical Information**

Default hinge	Left	Right
Voltage (V) I Current (A)	220-240   1.4	220-240   1.2
Made in	Germany	Germany

KEY: FS = Freestanding, NA = Not Applicable, \* = Freestanding side by sides consist of two Liebherr models. These models can be purchased separately. Cavity clearance for freestanding units please allow min. 50 mm above the unit if there is no ventilation cut-out.