## **SIDE BY SIDE COMBINATIONS**

**SBSes 7353** 







Quality, Design and Innovation



# SIDE BY SIDE COMBINATION SBSes 7353






Bio Fresh

lce Maker Smart Steel No Frost 3 Year Warranty





Whilst every effort is made to ensure all specifications and information in this flyer are correct at time of printing, Andi-Co Australia Pty. Ltd. reserve the right to make changes without notification. Where actual appliance measurements, specifications and ratings are crucial, we recommend that the actual appliance installation instructions that accompany each appliance be checked. Andi-Co Australia will not be liable for any loss.

Model	SBSes 7353*	
*Side-by-Sides comprised of two models	SBNes 3210	SKes 4210
Type I Finish	FS I SmartSteel <sup>o</sup>	FS I SmartSteel <sup>o</sup>
Energy consumption (kWh/yr) I Star rating	358kWh I 3.0	279kWh I 2.5
Compressors	1	1
Total capacity litres (L) - Gross I Net	321   276	405   391
Refrigerator gross (L) I Refrigerator net (L)	-	405   391
Freezer gross (L) I Freezer net (L)	150   119	-
BioFresh gross (L) I BioFresh net (L)	171 I 157	-
MagicEye control system I Display	SoftTouch I LCD	SoftTouch I LCD
Child proof setting for display & temp.	•	•
LED standard lighting	-	•
SlimLine handle - integrated opening device	•	•
Door open warning signal	•	•
Temperature alarm	•	-
Malfunction warning signal	•	•

#### **Refrigerator Features**

BioFresh drawers on telescopic rails	2	-
Fruit & vegetable drawer on telescopic rails	-	2
SuperCool	N/A	•
GlassLine shelves	•	•
Elegant holding columns	•	•
Removable VarioBoxes	N/A	•
Bottle shelf I Egg tray	- I N/A	•   •
Automatic refrigerator defrosting	•	•

#### **Freezer Features**

Frost Free	N/A
•	N/A
411	N/A
•	N/A
•	N/A
14	N/A
2	N/A
•	N/A
0.8	N/A
1.5	N/A
1.5	N/A
	• 411 • 14 2 • 0.8 1.5

### **Technical Information**

Default hinge	Left	Right
Voltage (V) I Rated Current (A)	220-240   1.4	220-240   1.2
Made in	Germany	Germany

KEY: FS = Freestanding, N/A = Not Applicable,  $^{o}$  = SmartSteel is only on doors,  $^{\star}$  = Freestanding side by sides consist of two Liebherr models. These models can be purchased separately. Cavity clearance for freestanding units please allow min. 50 mm above the unit if there is no ventilation cut-out.